

DEFENDER SERIES

PROJECTOR ENCLOSURE


Defender Series Enclosures are fully climate controlled and insulated. Taking care of hot, cold and humid environments, all in a closed loop sealed projector enclosure.

With a wide range of standard sizes and standard features, the Defender series enclosures can take on any projection project from 5000 Lumens to 50,000 lumens anywhere in the world.

DEFENDER FEATURES









PROTECT YOUR PROJECTOR









Model	Dimensions (inch) (LxWxH)	Power Draw*	Weight (lbs)	Door Opening (HxW)	Shipping Dimensions (LxWxH) / Weight	AC Wattage	Heating Wattage	Decibal Rating	Recommended Operating Temperature	Material	IP Rating
SMALL ENC-CC-SM	21.65 x 22.42 x 25.57	110v 5 amps	130	15.32" x 18.15"	33" x 26" x 30" (50 lbs crate) 180 lbs crated	500W	400W	55 db	-4°F ~ 131°F	Metal with powdercoat finish. White is the standard color. Custom colors available.	IP55 Equivalent
MEDIUM ENC-CC-MD	39.21 x 27.15 x 28.83	110v 10 amps	210	21.24" x 26.14"	43" x 33" x 35" (60 lbs crate) 270 lbs crated	1500W	400W	64 db			
LARGE ENC-CC-LG	54.17 x 35.24 x 33.44	110v 15 amps	230	26.02" x 41.10"	58" x 40" x 39" (90 lbs crate) 320 lbs crated	2500W	400W	68 db			
LARGE+ ENC-CC-LG+	62.64 x 47.56 x 41.83	110v 15 amps	560	34.38" x 55.75"	72" x 48" x 48" (141 lbs crate) 701 lbs crated	3500W	400W	70 db			
EXTRA LARGE ENC-CC-XL	75.25 x 53.25 x 46.25 (no unistrut)	220v 15 amps	802	56.00" x 43.25"	79" x 52" x 55" (100 lbs crate) 902 lbs crated	4500W	No Heater	68 db			
сиѕтом	Please Contact a representative										

^{*}Power draw does not account for the internal outlets.